

Material Safety Data Sheet

Version 5.0

Revision Date 04/21/2012

Print Date 07/05/2012

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : 2-Mercaptoethanol

Product Number : M6250

Brand : Aldrich

Supplier : Sigma-Aldrich
3050 Spruce Street
SAINT LOUIS MO 63103
USA

Telephone : +1 800-325-5832

Fax : +1 800-325-5052

Emergency Phone # (For both supplier and manufacturer) : (314) 776-6555

Preparation Information : Sigma-Aldrich Corporation
Product Safety - Americas Region
1-800-521-8956

2. HAZARDS IDENTIFICATION

Emergency Overview

OSHA Hazards

Combustible Liquid, Toxic by inhalation., Toxic by ingestion, Highly toxic by skin absorption, Skin sensitiser, Corrosive, Mutagen

Other hazards which do not result in classification

Stench., Rapidly absorbed through skin.

GHS Classification

Flammable liquids (Category 4)

Acute toxicity, Inhalation (Category 2)

Acute toxicity, Oral (Category 3)

Acute toxicity, Dermal (Category 2)

Skin irritation (Category 2)

Serious eye damage (Category 1)

Skin sensitization (Category 1)

Acute aquatic toxicity (Category 1)

Chronic aquatic toxicity (Category 1)

GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)

H227

Combustible liquid

H301

Toxic if swallowed.

H310 + H330

Fatal in contact with skin or if inhaled

H315

Causes skin irritation.

H317

May cause an allergic skin reaction.

H318

Causes serious eye damage.

H410

Very toxic to aquatic life with long lasting effects.

Precautionary statement(s)

P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/ eye protection/ face protection.
P284	Wear respiratory protection.
P302 + P350	IF ON SKIN: Gently wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/ physician.
P501	Dispose of contents/ container to an approved waste disposal plant.

HMIS Classification

Health hazard:	3
Chronic Health Hazard:	*
Flammability:	2
Physical hazards:	0

NFPA Rating

Health hazard:	3
Fire:	2
Reactivity Hazard:	0

Potential Health Effects

Inhalation	Toxic if inhaled. Material is extremely destructive to the tissue of the mucous membranes and upper respiratory tract.
Skin	May be fatal if absorbed through skin. Causes skin burns.
Eyes	Causes eye burns.
Ingestion	Toxic if swallowed.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms : Thioethylene glycol
2-Hydroxyethylmercaptan
BME
β-Mercaptoethanol

Formula : C₂H₆OS
Molecular Weight : 78.13 g/mol

Component		Concentration
2-Mercaptoethanol		
CAS-No.	60-24-2	-
EC-No.	200-464-6	

4. FIRST AID MEASURES

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

5. FIREFIGHTING MEASURES

Suitable extinguishing media

For small (incipient) fires, use media such as "alcohol" foam, dry chemical, or carbon dioxide. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

Special protective equipment for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

Hazardous combustion products

Hazardous decomposition products formed under fire conditions. - Carbon oxides, Sulphur oxides

Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Wear respiratory protection. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage temperature: 2 - 8 °C

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis
2-Mercaptoethanol	60-24-2	TWA	0.2 ppm	USA. Workplace Environmental Exposure Levels (WEEL)
Remarks	Skin			

Personal protective equipment

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Immersion protection
Material: butyl-rubber
Minimum layer thickness: 0.3 mm
Break through time: > 480 min
Material tested: Butoject® (Aldrich Z677647, Size M)

Splash protection
Material: Nature latex/chloroprene
Minimum layer thickness: 0.6 mm
Break through time: > 30 min
Material tested: Lapren® (Aldrich Z677558, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 873000, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an Industrial Hygienist familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Eye protection

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection

Complete suit protecting against chemicals. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form	liquid
Colour	colourless yellow

Safety data

pH	4.5 - 6 at 500 g/l at 20 °C (68 °F)
Melting point/freezing point	< -50 °C (< -58 °F)
Boiling point	157 °C (315 °F) - lit.
Flash point	68 °C (154 °F)
Ignition temperature	295 °C (563 °F) at 1,013 hPa (760 mmHg)
Autoignition temperature	no data available
Lower explosion limit	2.3 %(V)
Upper explosion limit	18 %(V)
Vapour pressure	0.76 hPa (0.57 mmHg) at 20 °C (68 °F) 4.67 hPa (3.50 mmHg) at 40 °C (104 °F)
Density	1.114 g/cm ³ at 25 °C (77 °F)
Water solubility	soluble
Partition coefficient: n-octanol/water	log Pow: -0.326 log Pow: -0.056 at 25 °C (77 °F)
Relative vapour density	2.70 - (Air = 1.0)

Odour	Stench.
Odour Threshold	no data available
Evaporation rate	no data available

10. STABILITY AND REACTIVITY

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

no data available

Conditions to avoid

Heat, flames and sparks.

Materials to avoid

Metals, Oxidizing agents

Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides, Sulphur oxides
Other decomposition products - no data available

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Oral LD50

LD50 Oral - rat - 98 - 162 mg/kg

Inhalation LC50

LC50 Inhalation - rat - 4 h - 2 mg/l

Dermal LD50

LD50 Dermal - rabbit - 112 - 224 mg/kg

Other information on acute toxicity

no data available

Skin corrosion/irritation

Skin - rabbit - Irritating to skin. - Draize Test

Serious eye damage/eye irritation

Eyes - rabbit - Risk of serious damage to eyes.

Respiratory or skin sensitization

Maximisation Test - guinea pig - OECD Test Guideline 406 - May cause sensitization by skin contact.

Germ cell mutagenicity

Experiments showed mutagenic effects in cultured bacterial cells.

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

no data available

Teratogenicity

no data available

Specific target organ toxicity - single exposure (Globally Harmonized System)

no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System)

no data available

Aspiration hazard

no data available

Potential health effects

Inhalation	Toxic if inhaled. Material is extremely destructive to the tissue of the mucous membranes and upper respiratory tract.
Ingestion	Toxic if swallowed.
Skin	May be fatal if absorbed through skin. Causes skin burns.
Eyes	Causes eye burns.

Signs and Symptoms of Exposure

burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea, Vomiting, Weakness, Unconsciousness, Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema

Synergistic effects

no data available

Additional Information

RTECS: KL5600000

12. ECOLOGICAL INFORMATION

Toxicity

Toxicity to fish	LC50 - Leuciscus idus (Golden orfe) - 46 - 100 mg/l - 96.0 h
Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia - 1.52 mg/l - 48 h EC50 - Daphnia - 0.89 mg/l - 48 h Method: OECD Test Guideline 202
Toxicity to algae	EC50 - Desmodesmus subspicatus (green algae) - 12 mg/l - 72 h
Toxicity to bacteria	LC50 - Bacteria - 125 mg/l - 17 h

Persistence and degradability

Biodegradability	Result: < 30.0 % - Not readily biodegradable. Result: 6 % - Not readily biodegradable. aerobic Result: < 10 % - Not readily biodegradable.
------------------	---

Bioaccumulative potential

Does not accumulate in organisms.

Mobility in soil

no data available

PBT and vPvB assessment

no data available

Other adverse effects

Biochemical Oxygen Demand (BOD) 105 mg/g

Chemical Oxygen Demand (COD) 1.894 mg/g

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

13. DISPOSAL CONSIDERATIONS**Product**

This combustible material may be burned in a chemical incinerator equipped with an afterburner and scrubber. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION**DOT (US)**

UN number: 2966 Class: 6.1 Packing group: II
Proper shipping name: Thioglycol
Marine pollutant: No
Poison Inhalation Hazard: No

IMDG

UN number: 2966 Class: 6.1 Packing group: II EMS-No: F-A, S-A
Proper shipping name: THIOGLYCOL
Marine pollutant: No

IATA

UN number: 2966 Class: 6.1 Packing group: II
Proper shipping name: Thioglycol

15. REGULATORY INFORMATION**OSHA Hazards**

Combustible Liquid, Toxic by inhalation., Toxic by ingestion, Highly toxic by skin absorption, Skin sensitiser, Corrosive, Mutagen

SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

2-Mercaptoethanol

CAS-No.
60-24-2

Revision Date
1993-04-24

Pennsylvania Right To Know Components

2-Mercaptoethanol

CAS-No.
60-24-2

Revision Date
1993-04-24

New Jersey Right To Know Components

CAS-No.

Revision Date

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION**Further information**

Copyright 2012 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.
